

AD-A083 892

FOREIGN TECHNOLOGY DIV WRIGHT-PATTERSON AFB OH
THE ADHESIVE COMPOSITION FOR PLASTICS.(U)
MAR 80

F/G 11/1

UNCLASSIFIED

FTD-ID(RS)T-0198-80

NL

[OF]
AD
50103-802



END
DATE
FILMED
6-80
DTIC

2

FTD-ID(RS)T-0198-80


AD A083892

FOREIGN TECHNOLOGY DIVISION



THE ADHESIVE COMPOSITION FOR PLASTICS

DTIC
ELECTE
MAY 5 1980
S B D



Approved for public release;
distribution unlimited.

FILE COPY

80 4 17 118

EDITED TRANSLATION

14 FTD-ID(RS)T-0198-80

11 28 Mar 1980

100
[4]

MICROFICHE NR: FTD-80-C-000400

6 THE ADHESIVE COMPOSITION FOR PLASTICS

English pages:

Source: Revista de Chimie
May 1976

Country of origin: (Romania) v27 n5 p432
Translated by: LINGUISTIC SYSTEMS, INC.

F33657-78-D-0618

Mina Winters

Requester: PHE

Approved for public release; distribution unlimited.

THIS TRANSLATION IS A RENDITION OF THE ORIGINAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DIVISION.

PREPARED BY:

TRANSLATION DIVISION
FOREIGN TECHNOLOGY DIVISION
WP-afb, OHIO.

14

mit

Journal of Chemistry

* Chemistry
* Chemical Engineering
* Chemical Equipment

Volume 27, May 1976, pages 373 -464

Publication of the Central Institute of Chemical Research
The Ministry of the Chemical Industry

Patent

The Adhesive Composition for Plastics
(Compoziția Adezivă pentru Materiale Plastice)

The Socialist Republic of Romania Patent Number 59583

The invention concerns the adhesive composition for plastics in general, and for polyethylene in special.

The adhesives known have the advantage that they form opaque gluing, limiting their use to only cases of non-transparent plates.

The adhesive composition, according to the invention, consists of a mix of two components:

- 75 - 97.5% grams polymers C_5 with a molecular weight of between 1500 and 2000, and an iodine value of between 160 and 200g/100g, with a viscosity of between 6,800 and 24,000 cP, at 20°C;
- 8.5 - 25% grams copolymer, grafted with maleic anhydride, with a molecular weight between 1,000 and 2,300, viscosity at 20°C of between 8,000 and 28,000 cP and a maleic anhydride of 15 - 18%.

The adhesive composition is transparent and practically colorless, it presents flexibility and resistance and it is used for plastics,

especially polyethylene.

File Number 62082

Int. cl: Cos 33/14

Registration date: 1/9/1970

Publication date: 11/30/1975

Authors: Eng. constantin Roncea
Dr. Eng. Mircea Corcovei
Dr. Eng. Victor Părăușeanu
Chemist Doru Mihăiță
Eng. Dumitru Nistor
Eng. Augustin Cotoagă

Holder of Title: "Policolor", Bucharest, manufacturers of varnishes
and dyestuff.

ACCESSION for	
NTIS	White Section <input checked="" type="checkbox"/>
DDC	Buff Section <input type="checkbox"/>
UNANNOUNCED	<input type="checkbox"/>
DISPOSITION	
BY	
DISTRIBUTION/AVAILABILITY CODES	
Dist. AVAIL. and/or SPECIAL	
A	